



INDUSTRIAL CYLINDER HEATED DRYING IRONERS WITH FRONT AND REAR RETURN (FCIR) AND LENGTH FOLDING (FCIF)

FCIR500 | FCIF500

FEATURES

- Large surface contact with linen over an angle of 300°
- Finger protection and emergency button for more safety
- Durable Meta Aramid ironing belts
- Automatic cooldown
- Easy to operate microprocessor: 20 pre-set ironing programs
- Indication of ironing speed and temperature
- Reverse mode possible
- Variable setups for folding (FCIF)
- Frequency-controlled motors
- Easy to remove lint filters
- Standard anti-static bar (FCIF)
- Folding system requires less maintenance (no ribbons and rolls)
- Electric, gas or steam heating
- FCIR model: front and rear output troughs
- FCIF model: front output table and integrated length folder



OPTIONS

- Foot pedal for easy stop and start operation
- Rear output table (FCIF)
- Output table (FCIR)
- Chrome-plated cylinder for a better thermal conduction



ROBUST
DESIGN



HIGH OUTPUT



LOW ENERGY
CONSUMPTION

THE SMART LAUNDRY PARTNER

	FCIF/FCIR 2000 / 500	FCIF/FCIR 2600 / 500	FCIF/FCIR 3200 / 500
ROLLER DIAMETER (MM)	502	502	502
USEFUL ROLLER LENGTH (MM)	2000	2600	3200
IRONING CAPACITY*			
ELECTRICAL AND GAS HEATING (KG/H)	80	95	120
STEAM HEATING (KG/H)	95	115	145
HEATING			
ELECTRIC (KW)	37,2	54	64,8
GAS (KW)	36	52	66
STEAM (KG/H)	49	68	88
MOTOR			
ROLLER MOTOR (KW)	0,37	0,37	0,37
FAN MOTOR (KW)	0,18 (50Hz) / 0,255 (60Hz)	2 x 0,18 (50Hz) / 2 x 0,255 (60Hz)	2 x 0,18(50Hz) / 2 x 0,255 (60Hz)
ROLLER SPEED (M/MIN)	1,5 - 8	1,5 - 8	1,5 - 8
ELECTRICAL CONNECTIONS			
	3 x 208-240V / 50-60Hz 3 x 380-415 + N/50-60Hz 3AC/380-415-N/50-60Hz 3AC/440/60Hz	3 x 208-240V / 50-60Hz 3 x 380-415 + N/50-60Hz 3AC/380-415-N/50-60Hz 3AC/440/60Hz	3 x 208-240V / 50-60Hz 3 x 380-415 + N/50-60Hz 3AC/380-415-N/50-60Hz 3AC/440/60Hz
TRANSPORT DATA			
NET WEIGHT (KG)	FCIR : 1090 (E) / 1140 (S) / 1230 (G) FCIF : 1150 (E) / 1200 (S) / 1290 (G)	FCIR : 1350 (E) / 1350 (S) / 1380 (G) FCIF : 1430 (E) / 1430 (S) / 1440 (G)	FCIR : 1490 (E) / 1520 (S) / 1580 (G) FCIF : 1590 (E) / 1620 (S) / 1680 (G)
GROSS WEIGHT (KG)	FCIR : 1330 (E) / 1370 (S) / 1460 (G) FCIF : 1460 (E) / 1510 (S) / 1600 (G)	FCIR : 1600 (E) / 1600 (S) / 1620 (G) FCIF : 1785 (E) / 1785 (S) / 1795 (G)	FCIR : 1810 (E) / 1840 (S) / 1900 (G) FCIF : 1990 (E) / 2020 (S) / 2080 (G)
DIMENSIONS H X W X D (MM)	FCIR : 1568 x 2750 x 1528 FCIF : 1568 x 2750 x 1620	FCIR : 1568 x 3350 x 1528 FCIF : 1568 x 3350 x 1620	FCIR : 1568 x 3950 x 1528 FCIF : 1568 x 3950 x 1620
PACKING DIMENSIONS H X W X D (MM)	1890 x 2885 x 1290	1890 x 3485 x 1290	1890 x 4085 x 1290

* Data from lab according to standard ISO9398-1. The actual capacity depends on laundry conditions and operators which could be 20% -40% lower.

