



INDUSTRIAL CYLINDER HEATED DRYING IRONERS

FCI800

FEATURES

- Large surface contact with linen
- Finger protection and emergency button for more safety
- Automatic cooldown
- Easy-to-operate microprocessor
- Overdimensioned fan for flexible installation
- Indication of ironing speed and temperature
- Reverse mode possible
- Frequency controlled motor
- Space saving installation against the wall is possible:
front return
- Electric, gas or steam heating
- Overheating check system



OPTIONS

- Stop pedal
- Vacuum table
- Auto adjustable ironing speed



ROBUST
DESIGN



HIGH OUTPUT



MODULAR
SYSTEM

THE SMART LAUNDRY PARTNER

FCI 3186 / 800	
ROLLER DIAMETER (MM)	800
USEFUL ROLLER LENGTH (MM)	3186
IRONING CAPACITY* (KG/H)	195
HEATING	
ELECTRICAL HEATING (KW)	75
GAS HEATING (KW)	110*
STEAM HEATING (KG/H)	190
MOTOR	
ROLLER MOTOR (KW)	0,9
FAN MOTOR (KW)	2 x 0,55(50Hz) / 2 x 0,75 (60Hz)
FAN CAPACITY (M³/H)	2 x 1300
ROLLER SPEED (M/MIN)	3 - 15
ELECTRICAL CONNECTIONS	
	380-415V 3AC+N 50/60 Hz 208-240V 3AC 50/60 Hz 380-415V 3AC-N 50/60 Hz 440-480V 3AC 60 Hz
TRANSPORT DATA	
NET WEIGHT (KG)	2610 (E) / 2900 (S) / 2480 (G)
GROSS WEIGHT (KG)	2870 (E) / 3160 (S) / 2740 (G)
DIMENSIONS H X W X D (MM)	1985 x 4260 x 1915
PACKING DIMENSIONS H X W X D (MM)	2080 x 4380 x 2080

* G20, 20mbar

**Data from lab according to standard ISO9398-1. The actual capacity depends on laundry conditions and operators which could be 20% -40% lower.

