

SIRIO 291

+ SIRIO 291



+ SIRIO CALZE/SOCKS



SIRIO 291



Revolving finishing cabinet with former providing excellent finishing quality for jackets, coats, dresses, etc. and topper shape for trousers, skirts etc. New microprocessor with 10 adjustable stored programs; for jackets and trousers two main programs with different times can be selected to work with automatic cycling succession for faster operation; Perfect thermal insulation of the door; Minimum floor encumbrance; Easy maintenance; Available either self-contained or for connection to central steam.

SIRIO SOCKS

Steam finishing cabinet for setting short, medium and long socks, of any type and size. The cycle length can vary from 30" to 180". Average production from 400 to 600 pcs per hour. 24 brackets on each side of the rotating door to be fitted for a total of 48 forms to be installed. It is advisable that flat forms have a minimum thickness of about 4 mm.



Available extras upon request SIRIO 291:

- two former shapes or two topper forms;
- external fan for accurate garment adjustment before cycle or for fast drying after cycle or for brushing operations;
- sliding trolley for legs instead of manual clamps;
- pneumatic waist-band expander instead of mechanical waist-band expander (connection to compressed air requested);
- pneumatic economizer device for a constant and ideal temperature in the cabinet.



Available extras upon request SIRIO SOCKS:

- brackets to fix socks forms;
- base to lift up the cabinet of about 10 cm to facilitate the operator's work.

TECHNICAL DATA	SIRIO 291 + BOILER	SIRIO 291
REQUIRED POWER	400 V/3+N/50 Hz* • 230 V/3/60 Hz*	230 V/1/50 Hz* • 110 V/1/60 Hz*
FAN MOTOR	0,75 kW	0,75 kW
PUMP MOTOR	0,5 kW	-
BOILER HEATING ELEMENTS	10 - 12 - 15 - 18 kW • 13,4 - 16 - 20,1 - 24,1 BHP	-
WATER FEEDING	rubber tube Ø 13mm • Ø 0,5 in	-
BOILER DRAIN	1/2 "	-
STEAM INLET	-	1/2 "
RETURN OUTLET	-	1/2 "
STEAM WORKING PRESSURE	5,5 bar - 72 psi	4 ÷ 6 bar - 58 ÷ 87 psi
STEAM CONSUMPTION	-	15 ÷ 20 kg/h - 33 ÷ 44 Lbs/h
FAN OUTLET	Ø 160 mm - Ø 6,3 in	Ø 160 mm - Ø 6,3 in
ENCUMBRANCE	1060 x 1180 mm - 42x45,5 in	1060 x 1180 mm - 42 x 45,5 in
NET WEIGHT WITH BOILER	210 kg - 462,9 Lbs	165 kg - 364 Lbs
GROSS WEIGHT PALLET + SPECIAL EXPORT CARTON	240 kg - 529,1 Lbs	195 kg - 430 Lbs
OVERALL DIMENSIONS	1190 x 900 x 2000 mm • 46,8 x 35,4 x 78,7 in	1180 x 900 x 2000 mm • 46,8 x 35,4 x 78,7 in
VOLUME	2,14 m3 - 75,5 ft3	2,14 m3 - 75,5 ft3

*Other voltages by request.

For manufacturing necessities the above-mentioned specifications are not binding.