

PRESSE LAVASECCO_CONFEZIONE

+ CT 750_B



+ CT 750_ULL



+ ST 702





PRESSES DRY-CLEANING_GARMENTS INDUSTRY

Wide range of professional finishing presses with a compact design, combining power, functionality and rapidity. Four different lines are produced to allow a rational and diversified choice, able to meet all requirements. Presses are available with different shaped heads and bucks both padded (steaming head and steam/vacuum buck; also blowing by request) or, in version L, with nickel-plated polished head (steaming and vacuum buck). All presses are ready for connection to external steam and vacuum supplies or available with built-in boiler (9 or 20 litres), compressor and vacuum. A balanced head using special self adjusting springs allowing optimal alignment of head and buck. On AT-770 SPECIAL and AT-770 models, the head opens to an angle of 60°. Copious and instant live steam production thanks to pneumatic valves for steam distribution to both the head and buck. Easy access to the controls with an adjustable pedal for the maximum comfort of the operator (AT-770 SPECIAL and AT-770).

AIR-OPERATED PRESSES

Air operated presses with either two button or pedal operated head closing complete with head safety guard.

CT 750

Excellently priced with brilliant performance; adjustable squeezing pressure.

AT 770

Professional performances with fast head movement and adjustable squeezing pressure.

AT 770_SPECIAL

Highly professional, with very fast head movement and extra strong adjustable squeezing pressure.



Available extras upon request:

- automatic system of the finishing cycle;
- blowing device on the buck;
- sponging/beating device, non-stop steam, adjustable spacing between head and buck;
- stainless steel arm and steam or steam/air spotting gun;
- steam iron assembly;
- anti-gloss plate for padded boards;
- nomex cloth for polished head (please note some accessories are model dependant).

TECHNICAL DATA	CT 750 - CT 750_L	AT 770 - AT 770_L	AT 770_SPECIAL AT 770_SPECIAL L
REQUIRED POWER	400V/3+N/50 Hz • 220V/3/60 Hz*		
9 LT BOILER HEATING	10 - 12 kW • 1-1,2 BHP		
20 LT BOILER HEATING	10 - 12 - 15 • 18 kW • 1 - 1,2 - 1,5 • 1,8 BHP		
PUMP MOTOR	0,5 kW	0,6 kW	
VACUUM MOTOR	0,25 kW	0,25 kW	
COMPRESSOR MOTOR	0,75 kW	1,1 kW	-
BOILER DRAIN	1/2"		
VACUUM EXHAUST	Ø100 mm • Ø4 in		
WATER FEEDING	Inner rubber tube Ø int. 13 mm • Ø 0,5 in		
STEAM INLET	1/2"		
CONDENSATION RETURN	1/2"		
STEAM WORKING PRESSURE	5 bar • 72,5 psi	5,5 bar • 79,7 psi	
STEAM CONSUMPTION	15 ÷ 20 kg/h • 33 ÷ 44 Lbs/h	14 ÷ 25 kg/h • 30,8 ÷ 55,1 Lbs/h	
COMPRESSED AIR INLET	3/8"		
AIR WORKING PRESSURE	8 ÷ 10 bar • 116 ÷ 145 psi	8 ÷ 10 bar • 100 psi	
COMPRESSED AIR CONSUMPTION	8 NL per cycle • 2,8 cubic feet/cycle	14 litri/ciclo • 4,9 cubic feet/cycle	
DIMENSIONS	1250 x 1060 mm • 49 x 42 in	1250 x 1150 mm • 49 x 45 in	
NET WEIGHT WITH BOILER	280 kg • 617 Lbs	374 kg • 824,5 Lbs	
GROSS WEIGHT PALLET + SPECIAL EXPORT CARTON	310 kg • 683 Lbs	405 kg • 897,8 Lbs	
PACKAGE DIMENSIONS	1380 x 1140 x 1440 mm • 54 x 45 x 57 in	1400 x 1120 x 1420 mm • 54 x 45 x 56 in	
VOLUME	2,27 m3 • 79,8 ft3	2,26 m3 • 79,8 ft3	

For manufacturing necessities the above-mentioned specifications are not binding.