

PRESSE LAVASECCO_CONFEZIONE

+ CT 750_B



+ CT 750_ULL



+ ST 702





PRESSES DRY-CLEANING_GARMENTS INDUSTRY

MANUAL PRESSES ST 702

Manually operated presses with manual control of head squeezing pressure producing excellent results while being very easy to use and maintain. A balanced head using special self adjusting springs allowing optimal alignment of head and buck. On CPS and CP models the head opens to an angle of 60°. Copious and instant live steam production thanks to pneumatic valves for steam distribution to both the head and buck. Easy access to the controls with an adjustable pedal for the maximum comfort of the operator (CPS and CP).



Available extras upon request:

- automatic system of the finishing cycle;
- blowing device on the buck;
- sponging/beating device, non-stop steam, adjustable spacing between head and buck;
- stainless steel arm and steam or steam/air spotting gun;
- steam iron assembly;
- anti-gloss plate for padded boards;
- nomex cloth for polished head (please note some accessories are model dependant).

TECHNICAL DATA	ST 702 - ST 702_L
REQUIRED POWER	400V/3+N/50 Hz • 220V/3/60 Hz*
9 LT BOILER HEATING	10 - 12 kW • 1-1,2 BHP
20 LT BOILER HEATING	10 - 12 - 15 • 18 kW • 1 - 1,2 - 1,5 • 1,8 BHP
PUMP MOTOR	0,5 kW
VACUUM MOTOR	0,25 kW
COMPRESSOR MOTOR	-
BOILER DRAIN	1/2"
VACUUM EXHAUST	Ø100 mm • Ø4 in
WATER FEEDING	Tubo gomma Ø interno • 13 mm Ø 0,5 in
STEAM INLET	1/2"
CONDENSATION RETURN	1/2"
STEAM WORKING PRESSURE	5 bar • 72,5 psi
STEAM CONSUMPTION	15 ÷ 20 kg/h • 33 ÷ 44 Lbs/h
COMPRESSED AIR INLET	-
AIR WORKING PRESSURE	-
COMPRESSED AIR CONSUMPTION	-
DIMENSIONS	1250 x 1150 mm • 49 x 45 in
NET WEIGHT WITH BOILER	355 kg • 783 Lbs
GROSS WEIGHT PALLET + SPECIAL EXPORT CARTON	385 kg • 849 Lbs
PACKAGE DIMENSIONS	1380 x 1140 x 1440 mm • 54 x 45 x 57 in
VOLUME	2,26 m3 • 79,8 ft3

For manufacturing necessities the above-mentioned specifications are not binding.