



BEST SOFT - MOUNT WASHER EXTRACTOR

FEATURES

- Heavy duty suspension & frame system
 - 30+ wash programs with large intuitive LCD display
 - Oversize loading and unloading door
 - Large bearing and water-seal provides excellent extract result.
 - Valued for efficiency
-
- Soft mount - lower installation cost
 - Extraction 300+G - reduces drying time
 - Frequency controlled motor
 - Stainless steel for all visible sides
 - Liquid soap ready
 - Easy-to-access internal parts for easy maintenance



INDUSTRIAL

SUSTAINABLE

EFFICIENCY

| AWE150 (15kg) | AWE200 (20kg) | AWE250 (25kg) | AWE300 (30kg) | AWE500 (50kg) | AWE1000 (100kg) |



STEAM HEATED	Unit	AWS150	AWS200	AWS250	AWS300	AWS500	AWS1000
Capacity	kg/lbs	15 / 35	20 / 45	25 / 55	30 / 70	50 / 110	100 / 220
Drum Diameter	mm	650	750	800	890	1020	1200
Drum Depth	mm	450	480	530	560	610	865
Drum Volume	Liter	150	200	250	348	500	980
DIMENSIONS							
Width	mm	910	1260	1260	1270	1630	1790
Depth	mm	1230	1200	1200	1450	1595	2025
Height	mm	1340	1400	1600	1630	1900	1940
WASHING / EXTRACTION							
Wash Speed	RPM	48	42	40	40	37	38
Distribution Speed	RPM	68	65	65	65	62	65
Low Extract Speed	RPM	400	400	400	400	400	400
High Extract Speed	RPM	920	850	820	800	750	700
Unloading Speed	RPM	15	15	15	15	15	15
G-factor	G	307	303	301	318	320	328
Standard Mode Cycle	Min	50	50	50	50	50	50
CONNECTIONS							
Cold Water Inlet	mm, in	25, 1"	25, 1"	25, 1"	25, 1"	40, 1 1/2"	50, 2"
Hot Water Inlet	mm, in	without	without	without	25, 1"	40, 1 1/2"	50, 2"
Steam Inlet	mm, in	15, 1/2"	25, 1"	25, 1"	25, 1"	25, 1"	25, 1"
Drain OD	mm	76	76	76	76	110	110
Drain for reuse OD	mm	without	without	without	76	110	110
Compressed Air OD	mm	8	8	8	8	8	8
PRESSURE							
Steam	Bar	.4~.6	.4~.6	.4~.6	.4~.6	.4~.6	.4~.6
Cold Water	Bar	.2~.3	.2~.3	.2~.3	.2~.3	.2~.3	.2~.3
Compressed Air	Bar	.4~.6	.4~.6	.4~.6	.4~.6	.4~.6	.4~.6
Power Supply							
Voltage	V	400	400	400	400	400	400
Frequency	Hz	50	50	50	50	50	50
Phase	Ph	3	3	3	3	3	3
Wire Copper	mm ²	2.5	2.5	4	4	4	6
Moto	Kw	2.2	2.5	2.5	3.2	5.5	7.5
Inverter	Kw	2.2	3.7	3.7	3.7	7.5	11
CONSUMPTION							
Water volume/cycle	L	320	360	390	580	900	1800
Steam kg/cycle	Kg	9	12	16	24	30	60
Electricity	Kw	0.45	0.35	0.55	0.65	1.1	1.7
Noise (decibel)	dB	<75	<75	<75	<75	<75	<75
Shipping Weight	Kg	650	750	850	1080	1800	3000
Versions in Electric Heat	Unit	AWE150	AWE200	AWE250	AWE300	AWE500	AWE1000
Capacity	kg/lbs	15 / 35	20 / 45	25 / 55	30 / 70	50 / 110	100 / 220
Voltage	V	400	400	400	400	400	400
Heating Element	Kw	9	12	18	18	27	63

ALKArashi LAUNDRY EQUIPMENTS

P. O. Box 84779, Al Qusais , Dubai, United Arab Emirates

+971505020676. E-mail: alka@wtssa.com